

View Online at <https://aerobasegroup.com/nsn/5910-00-436-2271>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

2.000 inches

Body Width:

1.305 inches

Body Height:

0.782 inches

Unthreaded Mounting Hole Diameter:

0.144 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.750 inches

Mounting Facility Type And Quantity:

4 unthreaded mounting holes

Capacitance Value Per Section:

600.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

180.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.25

Dc Leakage At Reference Temp:

22.500 microamperes

Terminal Surface Treatment:

Solder

Special Test Features:

Burn in

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0