Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-436-2313

## Body Style:

W/o mtg facilities terminal (s) on one surface

# Mil-std-1276 Wire Lead Type Designator:

N-1

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.250 inches

**Body Length:** 

0.500 inches

**Body Width:** 

0.500 inches

#### **Body Height:**

0.100 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.385 inches and 0.415 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

0.330 microfarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

## **Dissipation Factor At Reference Tempurature In Percent:**

2.0000

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-00-436-2313 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

