

View Online at <https://aerobasegroup.com/nsn/5910-00-436-2567>

Thread Class:

2a

Body Style:

Plate-meshing

Overall Length:

Between 1.328 inches and 1.390 inches

Bushing Diameter:

0.250 inches

Overall Height:

0.563 inches

Overall Width:

0.500 inches

Shaft Diameter:

0.187 inches single shaft

Bushing Length:

0.250 inches

Shaft Length:

0.250 inches single shaft

Body Length:

Between 0.828 inches and 0.890 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

50.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Quality Factor At 25 Deg Celsius:

1500.0

Fragility Factor:

Moderately rugged

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Uninclosed

Plate Quantity:

20

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Rotation:

180.0 degrees clockwise and 180.0 degrees counterclockwise

Adjustment Device Torque:

Between 2.500 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round

Plate Air Gap:

0.010 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Shaft Type:

Round, slotted single shaft

Capacitance Range In Picofarads:

+2.2/+34.0 single section

Nonderated Voltage Rating And Type:

650.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 shaft

Capacitance Drift In Picofarads:

0.20 single section

Material:

Steatite base

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0