NSN 5910-00-436-8370

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-436-8370

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
2.000 inches
Body Diameter:
0.562 inches
Body Length:
1.687 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
1725.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
5.100 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
300.0 dc single section
Tolerance Range Per Section:
-10.00/+50.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
12.0000
Dc Leakage At Reference Temp:
58.000 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
81349-mil-c-62+2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

2 uninsulated wire lead

Terminal Type And Quantity:

NSN 5910-00-436-8370

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0