NSN 5910-00-440-8952

Body Style:

Reliability Indicator:

Not established **Body Diameter:**0.562 inches **Body Length:**1.375 inches

2 tab, solder lug

W/thd mtg studs, axial terminals

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-440-8952

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.750 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting studs
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
10.0 megohm-microfarads
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.138 inches
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 dc single section
Tolerance Range Per Section:
-20.00 to 20.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
20000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:

NSN 5910-00-440-8952

Paper Dielectric Fixed Capacitor - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0