Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-441-7748

## Body Style:

W/o mtg facilities terminal (s) on one surface

# Mil-std-1276 Wire Lead Type Designator:

N-1

**Reliability Indicator:** 

Not established

#### Terminal Length:

1.250 inches

**Body Length:** 

0.500 inches

**Body Width:** 

0.500 inches

#### Body Height:

0.100 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.385 inches and 0.415 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

0.560 microfarads single section

### Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

## Dissipation Factor At Reference Tempurature In Percent:

2.5000

## **Terminal Surface Treatment:**

Solder

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0