NSN 5910-00-441-7752

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-441-7752

Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
0.281 inches
Body Diameter:
2.063 inches
Body Length:
4.500 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.190 inches
Terminal Diameter:
0.190 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
19.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
470.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
350.0 dc single section
Tolerance Range Per Section:
-10.00/+50.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
14.0000
Dc Leakage At Reference Temp:
610.000 microamperes
Case Insulation Material:
Plastic
Terminal Type And Quantity:

2 threaded hole

NSN 5910-00-441-7752

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0