

View Online at <https://aerobasegroup.com/nsn/5910-00-442-1255>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

1.250 inches

**Body Diameter:**

0.204 inches

**Body Length:**

0.814 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Etched foil

**Impedance At Minimum Operating Temperature In Ohms:**

250.0

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

15.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

34.0 milliamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

30.0 dc single section

**Tolerance Range Per Section:**

-15.00/+75.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

20.0000

**Dc Leakage At Reference Temp:**

6.000 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Test Data Document:**

94756-441-0992 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0