## NSN 5910-00-443-7885

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-443-7885 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** 0.400 inches **Body Width:** 0.440 inches **Body Height:** 0.180 inches **Continuous Current Rating In Amps:** 0.625 **Center To Center Distance Between Terminals Parallel To Length:** Between 0.268 inches and 0.332 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 4700.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 10000.0 megohms **Dissipation Factor At Reference Tempurature In Percent: Power Factor At Reference Tempurature In Percent:** 1.0000 **Quality Factor At Reference Temp:** 250.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 

Shelf Life: N/a

2 uninsulated wire lead

## NSN 5910-00-443-7885

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0