## NSN 5910-00-444-9249

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-444-9249

Body Style:
W/thd bushing mtg, terminals on opposite ends
Reliability Indicator:
Not established
Body Diameter:
0.235 inches
Body Length:
0.812 inches
Body Width:
0.235 inches
Body Height:
0.235 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Mounting Facility Type And Quantity:
1 threaded bushing
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
40000.0 megohm-microfarads
Capacitance Value Per Section:
1000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-120.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Tolerance Range Per Section:
-10.00 to 10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
250000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.1000
Terminal Surface Treatment:

Solder

## NSN 5910-00-444-9249

Plastic Dielectric Fixed Capacitor - Page 2 of 2



<b>Dielectric Material:</b>
Plastic polystyrene
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0