NSN 5910-00-445-2783

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-445-2783 |
|---|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 1.500 inches and 2.500 inches |
| Body Diameter: |
| Between 0.297 inches and 0.329 inches |
| Body Length: |
| Between 0.657 inches and 0.719 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Electrical Polarization: |
| Polarized |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 10.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -20.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+100.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5910-00-445-2783

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0