

View Online at https://aerobasegroup.com/nsn/5910-00-449-0127

Body Style: Chip type Reliability Indicator: Not established Terminal Length: Between 0.005 inches and 0.025 inches Body Length: Between 0.095 inches and 0.125 inches Body Width: Between 0.095 inches and 0.125 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section: 1 100 pixefarada single portion
Reliability Indicator: Not established Terminal Length: Between 0.005 inches and 0.025 inches Body Length: Between 0.095 inches and 0.125 inches Body Width: Between 0.095 inches and 0.125 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
Not established Terminal Length: Between 0.005 inches and 0.025 inches Body Length: Between 0.095 inches and 0.125 inches Body Width: Between 0.095 inches and 0.125 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
Terminal Length:Between 0.005 inches and 0.025 inchesBody Length:Between 0.095 inches and 0.125 inchesBody Width:Between 0.095 inches and 0.125 inchesBody Height:0.100 inchesSchematic Diagram Designator:No common or grounded electrode (s)Insulation Resistance At Maximum Operating Temp:100000.0 megohmsCapacitance Value Per Section:
Between 0.005 inches and 0.025 inches Body Length: Between 0.095 inches and 0.125 inches Body Width: Between 0.095 inches and 0.125 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
Body Length:Between 0.095 inches and 0.125 inchesBody Width:Between 0.095 inches and 0.125 inchesBody Height:0.100 inchesSchematic Diagram Designator:No common or grounded electrode (s)Insulation Resistance At Maximum Operating Temp:100000.0 megohmsCapacitance Value Per Section:
Between 0.095 inches and 0.125 inches Body Width: Between 0.095 inches and 0.125 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
Body Width: Between 0.095 inches and 0.125 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
Between 0.095 inches and 0.125 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
Insulation Resistance At Maximum Operating Temp: 100000.0 megohms Capacitance Value Per Section:
100000.0 megohms Capacitance Value Per Section:
Capacitance Value Per Section:
1 100 piceforade single section
1.100 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
90.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Tolerance Range Per Section:
-0.10/+0.10 picofarads single section
Case Material:
Ceramic
Insulation Resistance At Reference Temp:
1000000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.050
Quality Factor At Reference Temp:
10000.000
Terminal Surface Treatment:
Palladium and silver
Precious Material And Location:
Terminal surfaces palladium and terminal surfaces silver
Terminal Type And Quantity:
2 bonding pad



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0