## NSN 5910-00-449-0210

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-449-0210

view Online at https://aerobasegroup.com/nsn/5910-00-449-0210
Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.395 inches
Body Length:
0.703 inches
Body Width:
0.750 inches
Body Height:
0.875 inches
Center To Center Distance Between Terminals Parallel To Length:
0.374 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Etched foil
Impedance At Minimum Operating Tempurature In Ohms:
57.0
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
60.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
200.0 microamperes
Nonderated Continuous Voltage Rating And Type Per Section:
75.0 dc single section
Tolerance Range Per Section:
-15.00/+75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
20.0000

Dc Leakage At Reference Temp:

23.000 microamperes

## NSN 5910-00-449-0210

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
1 solder stud and 1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0