

View Online at https://aerobasegroup.com/nsn/5910-00-449-0276

| Body Style: | |
|------------------|--|
| Rotary | |
| Body Length: | |
| 0.250 inches | |
| Body Height: | |
| 0.156 inches | |
| Tempurature | Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| 0.0 single sect | ion |
| Tempurature | Coefficient Of Capacitance Range In Ppm Per Deg Celsius: |
| -150.0 to 150.0 |) single section |
| Distance Betv | veen Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.200 inches | |
| Quality Factor | r At 25 Deg Celsius: |
| 500.0 | |
| Inclosure Typ | e: |
| Encased | |
| Adjustment D | evice Torque: |
| Between 1.000 |) inch-ounces and 5.000 inch-ounces |
| Insulation Dc | Resistance At 25 Deg Celsius: |
| 10000.0 kilohm | ns |
| Mounting Fac | ility Type And Quantity: |
| 2 terminal | |
| Nonderated O | perating Temp: |
| Between -55.0 | degrees celsius and 85.0 degrees celsius |
| Capacitance F | Range In Picofarads: |
| +1.6 to 9.0 sing | gle section |
| Nonderated V | oltage Rating And Type: |
| 50.0 dc continu | uous single section |
| Adjustment D | evice Drive Type And Quantity: |
| 1 slotted screw | 1 |
| Terminal Type | e And Quantity: |
| 2 wire lead | |
| Shelf Life: | |
| N/a | |
| Unit Of Measu | ire: |
| | |
| Demilitarizatio | on: |
| No | |
| Fiig: | |
| A096a0 | |