## NSN 5910-00-449-7922

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-449-7922 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.312 inches **Body Length:** 1.062 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Etched foil **Impedance At Minimum Operating Tempurature In Ohms:** 847.0 **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 4.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Dc Leakage At Maximum Operating Temp: 36.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -15.00/+30.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent:** 15.0000 Dc Leakage At Reference Temp: 4.000 microamperes **Terminal Surface Treatment:** 

Solder **Case Insulation Material: Plastic** 

## NSN 5910-00-449-7922

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type A	and Quantity	<b>/</b> :
-----------------	--------------	------------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0