## NSN 5910-00-449-8514

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-449-8514
Reliability Indicator:
Not established
Center To Center Distance Between Terminals Parallel To Length:
Between 1.410 inches and 1.450 inches
Center To Center Distance Between Terminals Parallel To Width:
Between 0.620 inches and 0.680 inches
Terminal Height From Body:
0.200 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.440 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.620 inches and 0.680 inches
Mounting Facility Type And Quantity:
4 threaded mounting holes
Section Quantity:
2
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
1.000 microfarads all sections
Nonderated Continuous Voltage Rating And Type Per Section:
208.0 ac-rms all sections
Tolerance Range Per Section:
-10.00/+10.00 percent all sections
Case Material:
Metal
Insulation Resistance At Reference Temp:
5000.0 megohm-microfarads
Terminal Type And Quantity:
4 standoff, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0