

View Online at <https://aerobasegroup.com/nsn/5910-00-449-8525>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

Between 0.325 inches and 0.335 inches

Body Length:

Between 3.812 inches and 3.938 inches

Body Width:

Between 1.000 inches and 1.126 inches

Body Height:

Between 1.000 inches and 1.126 inches

Terminal Diameter:

Between 0.120 inches and 0.130 inches

Unthreaded Mounting Hole Diameter:

0.161 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.859 inches and 2.891 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.435 inches

Mounting Facility Type And Quantity:

4 unthreaded mounting holes

Capacitance Value Per Section:

3300.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

570.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Power Factor At Reference Tempurature In Percent:

30.000

Dc Leakage At Reference Temp:

95.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0