

View Online at <https://aerobasegroup.com/nsn/5910-00-449-8525>

**Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.325 inches and 0.335 inches

**Body Length:**

Between 3.812 inches and 3.938 inches

**Body Width:**

Between 1.000 inches and 1.126 inches

**Body Height:**

Between 1.000 inches and 1.126 inches

**Terminal Diameter:**

Between 0.120 inches and 0.130 inches

**Unthreaded Mounting Hole Diameter:**

0.161 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.859 inches and 2.891 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Electrical Polarization:**

Polarized

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.435 inches

**Mounting Facility Type And Quantity:**

4 unthreaded mounting holes

**Capacitance Value Per Section:**

3300.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

570.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

25.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Power Factor At Reference Tempurature In Percent:**

30.000

**Dc Leakage At Reference Temp:**

95.000 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0