# NSN 5910-00-451-5530

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-451-5530

## Body Style:

W/o mtg facilities, axial terminals

# Mil-std-1276 Wire Lead Type Designator:

N-2

**Reliability Indicator:** 

Not established

## **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.332 inches

## **Body Length:**

0.813 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## **Features Provided:**

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

1000.0 megohm-microfarads

## **Capacitance Value Per Section:**

1.000 microfarads single section

## Nonderated Operating Temp:

Between -62.0 degrees celsius and 100.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

30.0 dc single section

## **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

## **Case Material:**

Metal

## Insulation Resistance At Reference Temp:

300000.0 megohm-microfarads

## **Dissipation Factor At Reference Tempurature In Percent:**

0.2000

# **Terminal Surface Treatment:**

Gold

# Case Insulation Material:

Plastic

# **Special Features:**

Level b quality assurance

# Precious Material And Location:

Terminal surface gold

# Terminal Type And Quantity:

2 uninsulated wire lead

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0