NSN 5910-00-451-5532



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-451-5532 **Body Style:** W/o mtg facilities, axial terminals Mil-std-1276 Wire Lead Type Designator: N-2 **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.332 inches **Body Length:** 0.687 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohm-microfarads **Capacitance Value Per Section:** 0.470 microfarads single section **Nonderated Operating Temp:** Between -62.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:**

300000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.2000 **Terminal Surface Treatment:** Gold **Case Insulation Material: Plastic Special Features:** Level b quality assurance **Precious Material And Location:** Terminal surface gold **Terminal Type And Quantity:** 2 uninsulated wire lead

NSN 5910-00-451-5532

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Domilitarization

Demilitarization:

No

Fiig:

A010b0