NSN 5910-00-452-0921

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-452-0921 **Body Style:** Piston **Overall Length:** 2.172 inches **Bushing Diameter:** 0.190 inches **Overall Height:** Between 0.191 inches and 0.195 inches **Shaft Diameter:** 0.167 inches single shaft **Bushing Length:** 0.281 inches **Shaft Length:** 0.125 inches single shaft **Body Length:** 1.766 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 250.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encapsulated **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Insulation Dc Resistance At Max Operating Temp:** 100.0 gigohms **Bushing Width:** Between 0.171 inches and 0.175 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.190 inches

NSN 5910-00-452-0921

A096a0

Glass Dielectric Variable Capacitor - Page 2 of 2



Shaft Type:
Round, slotted single shaft
Capacitance Range In Picofarads:
+1.0/+120.0 single section
Nonderated Voltage Rating And Type:
1000.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Capacitance Drift In Picofarads:
0.50 single section
Test Data Document:
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
1 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: