## NSN 5910-00-453-7864

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-453-7864

**Body Style:** 

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.500 inches

**Body Diameter:** 

0.478 inches

**Body Length:** 

1.001 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

40000.0 megohms

**Capacitance Value Per Section:** 

20000.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-50.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-50.0/+50.0 single section

**Tolerance Range Per Section:** 

-1.00/+1.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1000

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Test Data Document:** 

94756-441-1033 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-453-7864

Plastic Dielectric Fixed Capacitor - Page 2 of 2



SI	hel	f L	ife	:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0