Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-453-8883

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

## **Body Diameter:**

0.207 inches

## **Body Length:**

0.955 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Anode Type:

Solid

## **Electrical Polarization:**

Nonpolarized

## **Features Provided:**

Hermetically sealed case

## **Capacitance Value Per Section:**

5.000 microfarads single section

## Nonderated Operating Temp:

Between -80.0 degrees celsius and 85.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

20.0 milliamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

## **Case Material:**

Metal

## **Capacitive Electrode Material:**

Tantalum

# Dissipation Factor At Reference Tempurature In Percent:

6.0000

# Power Factor At Reference Tempurature In Percent:

10.0000

# Dc Leakage At Reference Temp:

1.500 milliamperes

# Case Insulation Material:

Plastic

# **Test Data Document:**

06845-2088234 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Electrolytic Fixed Capacitor - Page 2 of 2



# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0