NSN 5910-00-454-7256

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-454-7256

Body Style:					
W/o mtg facilities, terminal (s) on one surface					
Reliability Indicator:					
Not established					
Body Length:					
4.563 inches					
Body Width:					
3.750 inches					
Body Height:					
Between 7.187 inches and 7.313 inches					
Center To Center Distance Between Terminals Parallel To Length:					
2.000 inches					
Terminal Diameter:					
0.190 inches					
Terminal Height From Body:					
1.000 inches					
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:					
2.000 inches					
Schematic Diagram Designator:					
Series connected					
Internal Electrical Connection Type:					
Internal Electrical Connection Type: Inserted tab					
Inserted tab					
Inserted tab Mounting Facility Screw Thread Series Designator:					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity:					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section:					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section Nonderated Operating Temp:					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section Nonderated Operating Temp: 70.0 degrees celsius					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section Nonderated Operating Temp: 70.0 degrees celsius Thread Size:					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section Nonderated Operating Temp: 70.0 degrees celsius Thread Size: 0.190 inches					
Inserted tab Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section Nonderated Operating Temp: 70.0 degrees celsius Thread Size: 0.190 inches Nonderated Continuous Voltage Rating And Type Per Section:					
Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section Nonderated Operating Temp: 70.0 degrees celsius Thread Size: 0.190 inches Nonderated Continuous Voltage Rating And Type Per Section: 330.0 ac-rms single section					
Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section Nonderated Operating Temp: 70.0 degrees celsius Thread Size: 0.190 inches Nonderated Continuous Voltage Rating And Type Per Section: 330.0 ac-rms single section Tolerance Range Per Section:					
Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section Nonderated Operating Temp: 70.0 degrees celsius Thread Size: 0.190 inches Nonderated Continuous Voltage Rating And Type Per Section: 330.0 ac-rms single section Tolerance Range Per Section: -6.00 to 6.00 percent single section					
Mounting Facility Screw Thread Series Designator: Unf Mounting Facility Type And Quantity: 2 threaded mounting studs Capacitance Value Per Section: 81.000 microfarads single section Nonderated Operating Temp: 70.0 degrees celsius Thread Size: 0.190 inches Nonderated Continuous Voltage Rating And Type Per Section: 330.0 ac-rms single section Tolerance Range Per Section: -6.00 to 6.00 percent single section Case Material:					

N/a

Shelf Life:

NSN 5910-00-454-7256

Paper Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0