## NSN 5910-00-460-8804

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-460-8804

W/thd mtg hol (s)/stud(s), terminal(s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.172 inches
Body Length:
1.435 inches
Body Width:
1.715 inches
Body Height:
1.155 inches
Center To Center Distance Between Terminals Parallel To Length:
0.812 inches
Terminal Diameter:
0.094 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.312 inches
Schematic Diagram Designator:
One terminal common to each section
Mounting Facility Screw Thread Series Designator:
mounting the many colon time and collections and collections
Unf
Unf
Unf Mounting Facility Type And Quantity:
Unf  Mounting Facility Type And Quantity: 4 threaded mounting holes
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity:
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2 Capacitance Value Per Section:
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2 Capacitance Value Per Section: 15.000 microfarads all sections
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2 Capacitance Value Per Section: 15.000 microfarads all sections Nonderated Operating Temp:
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2 Capacitance Value Per Section: 15.000 microfarads all sections Nonderated Operating Temp: Between -55.0 degrees celsius and 110.0 degrees celsius
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2 Capacitance Value Per Section: 15.000 microfarads all sections Nonderated Operating Temp: Between -55.0 degrees celsius and 110.0 degrees celsius Thread Size:
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2 Capacitance Value Per Section: 15.000 microfarads all sections Nonderated Operating Temp: Between -55.0 degrees celsius and 110.0 degrees celsius Thread Size: 0.112 inches
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2 Capacitance Value Per Section: 15.000 microfarads all sections Nonderated Operating Temp: Between -55.0 degrees celsius and 110.0 degrees celsius Thread Size: 0.112 inches Nonderated Continuous Voltage Rating And Type Per Section:
Unf Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2 Capacitance Value Per Section: 15.000 microfarads all sections Nonderated Operating Temp: Between -55.0 degrees celsius and 110.0 degrees celsius Thread Size: 0.112 inches Nonderated Continuous Voltage Rating And Type Per Section: 180.0 dc all sections
Mounting Facility Type And Quantity: 4 threaded mounting holes Section Quantity: 2 Capacitance Value Per Section: 15.000 microfarads all sections Nonderated Operating Temp: Between -55.0 degrees celsius and 110.0 degrees celsius Thread Size: 0.112 inches Nonderated Continuous Voltage Rating And Type Per Section: 180.0 dc all sections Tolerance Range Per Section:
Mounting Facility Type And Quantity:  4 threaded mounting holes  Section Quantity:  2  Capacitance Value Per Section:  15.000 microfarads all sections  Nonderated Operating Temp:  Between -55.0 degrees celsius and 110.0 degrees celsius  Thread Size:  0.112 inches  Nonderated Continuous Voltage Rating And Type Per Section:  180.0 dc all sections  Tolerance Range Per Section: -10.00/+10.00 percent all sections

Solder

5000.0 megohms

**Terminal Surface Treatment:** 

## NSN 5910-00-460-8804

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



## **Test Data Document:**

82260-8814100001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

4 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0