

View Online at <https://aerobasegroup.com/nsn/5910-00-461-8277>

Body Style:

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.250 inches

Body Length:

1.125 inches

Body Width:

1.750 inches

Body Height:

1.125 inches

Center To Center Distance Between Terminals Parallel To Length:

0.344 inches

Terminal Diameter:

0.090 inches

Unthreaded Mounting Hole Diameter:

0.144 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.843 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Polarized

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.828 inches

Mounting Facility Type And Quantity:

3 unthreaded mounting holes

Capacitance Value Per Section:

890.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

35.0 dc single section

Tolerance Range Per Section:

-10.00/+30.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

6.0000

Dc Leakage At Reference Temp:

200.000 microamperes

Case Insulation Material:

Plastic

Special Features:

Item has two mounting brackets bonded to it

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0