NSN 5910-00-462-5714



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-462-5714 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.327 inches **Body Length:** 1.000 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Etched foil **Impedance At Minimum Operating Tempurature In Ohms:** 1250.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 1.800 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 100.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material: Equivalent Series Resistance At Reference Tempurature In Ohms:** 135.00 Dc Leakage At Reference Temp: 14.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:**

Plastic

Special Test Features:

Burn-in

NSN 5910-00-462-5714

Electrolytic Fixed Capacitor - Page 2 of 2



Test Data Document:

95542-908243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0