Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-462-5714

# **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

# Terminal Length:

1.500 inches

#### **Body Diameter:**

0.327 inches

#### **Body Length:**

1.000 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Anode Type:

Etched foil

# Impedance At Minimum Operating Tempurature In Ohms:

1250.0

# **Electrical Polarization:**

Polarized

# Capacitance Value Per Section:

1.800 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Dc Leakage At Maximum Operating Temp:

100.0 milliamperes

#### Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### Case Material:

Metal

#### **Capacitive Electrode Material:**

Tantalum

#### Equivalent Series Resistance At Reference Tempurature In Ohms:

135.00

#### Dc Leakage At Reference Temp:

14.000 microamperes

# **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Plastic

# **Special Test Features:**

Burn-in

# NSN 5910-00-462-5714

Electrolytic Fixed Capacitor - Page 2 of 2



#### **Test Data Document:**

95542-908243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A010b0