

View Online at https://aerobasegroup.com/nsn/5910-00-464-9859

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

# **Terminal Length:**

1.250 inches

#### **Body Diameter:**

0.140 inches

**Body Length:** 

0.390 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

### 0.220 microfarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

# **Case Material:**

Ceramic

#### Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

## **Dissipation Factor At Reference Tempurature In Percent:**

2.5000

#### **Terminal Surface Treatment:**

Solder

#### **Test Data Document:**

81349-mil-c-11015+20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A010b0