

View Online at <https://aerobasegroup.com/nsn/5910-00-466-1231>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

1.620 inches

Body Length:

0.185 inches

Body Width:

0.225 inches

Body Height:

0.075 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.130 inches and 0.170 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

Capacitance Value Per Section:

4.700 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

6.0000

Dc Leakage At Reference Temp:

1.200 microamperes

Terminal Surface Treatment:

Solder

Special Test Features:

Burn-in

Test Data Document:

97942-580r596 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0