## NSN 5910-00-469-3262

Quartz Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-469-3262 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 2.281 inches **Bushing Diameter:** 0.250 inches **Shaft Diameter:** 0.188 inches single shaft **Bushing Length:** 0.250 inches **Shaft Length:** 0.656 inches single shaft **Body Length:** 1.219 inches **Overall Diameter:** 0.375 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 25.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -25.0/+25.0 single section **Quality Factor At 25 Deg Celsius:** 1500.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 100.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 150.0 degrees celsius **Thread Size:** 0.250 inches **Shaft Type:** Round, slotted single shaft **Capacitance Range In Picofarads:** 

+0.8/+10.0 single section

## NSN 5910-00-469-3262

Quartz Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Type:
5000.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Terminal Type And Quantity:
2 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A096a0