NSN 5910-00-469-5820

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-469-5820

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
Between 1.120 inches and 1.220 inches
Body Width:
Between 0.430 inches and 0.530 inches
Body Height:
Between 0.590 inches and 0.690 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.500 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
Tolerance Range Per Section: -5.00/+5.00 percent single section
-
-5.00/+5.00 percent single section
-5.00/+5.00 percent single section Case Material:
-5.00/+5.00 percent single section Case Material: Plastic
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.500
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.500 Terminal Surface Treatment:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.500 Terminal Surface Treatment: Solder
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.500 Terminal Surface Treatment: Solder Dielectric Material:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.500 Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.500 Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.500 Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity: 2 uninsulated wire lead
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.500 Terminal Surface Treatment: Solder Dielectric Material: Plastic polycarbonate Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:

No

Demilitarization:

NSN 5910-00-469-5820

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0