

View Online at <https://aerobasegroup.com/nsn/5910-00-471-8448>

Body Style:

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

2.392 inches

Body Width:

1.187 inches

Body Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.875 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Impedance At Minimum Operating Temperature In Ohms:

10.0

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

4 threaded mounting studs

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

240.000 microfarads single section

Nonderated Operating Temp:

Between -85.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.138 inches

Dc Leakage At Maximum Operating Temp:

120.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

110.0 dc single section

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dc Leakage At Reference Temp:

48.000 microamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0