

View Online at <https://aerobasegroup.com/nsn/5910-00-472-5005>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

0.202 inches

Terminal Length:

0.365 inches

Body Length:

0.359 inches

Terminal Diameter:

0.051 inches

Schematic Diagram Designator:

Feedthrough

End Application:

Virginia class cgn (41); tarawa class lha; spruance class dd (963); wasp class lhd; ticonderoga class cg (47); austin ship class lpd-4 amphibious transport docks; oliver perry ffg; forrestal class cv; nimitz class cvn; kidd class ddg

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

10.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-10.0/+10.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Power Factor At Reference Temperature In Percent:

3.5000

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

1 solder stud and 1 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0