NSN 5910-00-473-1878

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-473-1878 |
|--|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Established |
| Terminal Length: |
| 1.250 inches |
| Body Length: |
| 0.160 inches |
| Body Width: |
| 0.070 inches |
| Body Height: |
| 0.070 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 10000.0 megohms |
| Capacitance Value Per Section: |
| 4700.000 picofarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -15.0/+15.0 without voltage applied single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Terminal Surface Treatment: |
| Solder |
| Test Data Document: |
| 81349-milc39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . |

No

Demilitarization:

NSN 5910-00-473-1878

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0