

View Online at <https://aerobasegroup.com/nsn/5910-00-476-0591>

Thread Class:

2a

Body Style:

Piston

Overall Length:

Between 1.598 inches and 2.176 inches

Terminal Length:

0.230 inches

Bushing Length:

Between 0.312 inches and 0.890 inches

Body Length:

1.286 inches

Overall Diameter:

0.370 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Fragility Factor:

Moderately rugged

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

10000000.0 megohms

Bushing Width:

0.250 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 150.0 degrees celsius

Thread Size:

0.250 inches

Capacitance Range In Picofarads:

+0.6/+12.0 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.01 single section

Material:

Quartz inclosure

Terminal Type And Quantity:

1 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0