

View Online at <https://aerobasegroup.com/nsn/5910-00-477-7993>

Body Style:

W/twist tab mtg, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

0.421 inches

Body Diameter:

1.390 inches

Body Length:

4.547 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Los angeles class ssn (688), ticonderoga class cg (47), kidd class ddg, seawolf class ssn, spruance class dd (963), virginia class cgn (41). General purpose electronic test equipment (gpete).

Section Quantity:

2

Capacitance Value Per Section:

3500.000 microfarads 1st section

Nonderated Operating Temp:

Between -20.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc 2nd section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00 to 100.00 percent all sections

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dc Leakage At Reference Temp:

100.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0