NSN 5910-00-478-1226

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-478-1226

Body Style: W/thd bushing mtg, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.296 inches **Body Diameter:** 0.416 inches **Body Length:** 0.830 inches **Schematic Diagram Designator:** Electrod (s) grounded to case **Mounting Facility Screw Thread Series Designator:** Unf **Mounting Facility Type And Quantity:** 1 threaded bushing **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 40000.0 megohm-microfarads **Capacitance Value Per Section:** 0.012 microfarads single section **Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.312 inches

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-120.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Tolerance Range Per Section:

-1.00/+1.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

250000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

0.1000

Terminal Surface Treatment:

Solder

NSN 5910-00-478-1226

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Dielectric Material:
Plastic polystyrene
Terminal Type And Quantity:
1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0