## NSN 5910-00-478-1240

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-478-1240 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.250 inches **Body Length:** 0.852 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 40000.0 megohm-microfarads **Capacitance Value Per Section:** 4700.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -120.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 250000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.1000 **Terminal Surface Treatment:** Solder **Case Insulation Material:** Plastic **Terminal Type And Quantity:** 2 uninsulated wire lead

Shelf Life: N/a

## NSN 5910-00-478-1240

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0