

View Online at <https://aerobasegroup.com/nsn/5910-00-478-3457>

Body Style:

Rotary

Body Diameter:

0.218 inches

Body Height:

0.175 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-55.0 to 125.0 single section

Center To Center Distance Between Terminals Parallel To Diameter:

0.195 inches

Quality Factor At 25 Deg Celsius:

500.0

Inclosure Type:

Encased

Adjustment Device Rotation:

180.0 degrees clockwise

Adjustment Device Torque:

Between 0.500 inch-ounces and 3.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10.0 gigohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+2.5 to 9.0 single section

Nonderated Voltage Rating And Type:

100.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-1.50 to 1.50 and -1.50 to 1.50 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.50 single section

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0