

View Online at <https://aerobasegroup.com/nsn/5910-00-479-6793>

**Thread Class:**

2a

**Body Style:**

Piston

**Overall Length:**

Between 1.813 inches and 1.875 inches

**Terminal Length:**

1.500 inches

**Bushing Diameter:**

0.250 inches

**Shaft Diameter:**

0.250 inches single shaft

**Bushing Length:**

0.250 inches

**Shaft Length:**

0.500 inches single shaft

**Body Length:**

Between 1.344 inches and 1.406 inches

**Overall Diameter:**

0.375 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

0.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-100.0/+100.0 single section

**Center To Center Distance Between Terminals Parallel To Length:**

1.016 inches

**Terminal Diameter:**

0.032 inches

**Quality Factor At 25 Deg Celsius:**

20000.0

**Fragility Factor:**

Moderately rugged

**Terminal Width:**

0.130 inches

**Terminal Thickness:**

0.015 inches

**Mounting Facility Screw Thread Series Designator:**

Unef

**Inclosure Type:**

Encased

**Adjustment Device Torque:**

Between 1.000 inch-ounces and 10.000 inch-ounces

**Bushing Shape:**

Round

**Insulation Dc Resistance At 25 Deg Celsius:**

1000000.0 megohms

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 200.0 degrees celsius

**Thread Size:**

0.250 inches

**Shaft Type:**

Round, slotted single shaft

**Capacitance Range In Picofarads:**

+0.5/+5.0 single section

**Nonderated Voltage Rating And Type:**

2000.0 ac peak single section

**Adjustment Device Drive Type And Quantity:**

1 shaft

**Capacitance Drift In Picofarads:**

0.04 single section

**Material:**

Quartz capacitive electrode

**Terminal Type And Quantity:**

1 tab, solder lug and 1 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0