

View Online at <https://aerobasegroup.com/nsn/5910-00-479-6793>

Thread Class:

2a

Body Style:

Piston

Overall Length:

Between 1.813 inches and 1.875 inches

Terminal Length:

1.500 inches

Bushing Diameter:

0.250 inches

Shaft Diameter:

0.250 inches single shaft

Bushing Length:

0.250 inches

Shaft Length:

0.500 inches single shaft

Body Length:

Between 1.344 inches and 1.406 inches

Overall Diameter:

0.375 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Center To Center Distance Between Terminals Parallel To Length:

1.016 inches

Terminal Diameter:

0.032 inches

Quality Factor At 25 Deg Celsius:

20000.0

Fragility Factor:

Moderately rugged

Terminal Width:

0.130 inches

Terminal Thickness:

0.015 inches

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 200.0 degrees celsius

Thread Size:

0.250 inches

Shaft Type:

Round, slotted single shaft

Capacitance Range In Picofarads:

+0.5/+5.0 single section

Nonderated Voltage Rating And Type:

2000.0 ac peak single section

Adjustment Device Drive Type And Quantity:

1 shaft

Capacitance Drift In Picofarads:

0.04 single section

Material:

Quartz capacitive electrode

Terminal Type And Quantity:

1 tab, solder lug and 1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0