

View Online at <https://aerobasegroup.com/nsn/5910-00-479-7947>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

Between 8.000 inches and 8.500 inches

Body Diameter:

0.578 inches

Body Length:

0.744 inches

Terminal Diameter:

Between 0.041 inches and 0.047 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Anode Type:

Solid

Impedance At Minimum Operating Tempurature In Ohms:

53.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

60.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

25.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-15.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Tempurature In Percent:

19.000

Equivalent Series Resistance At Reference Tempurature In Ohms:

4.00

Dc Leakage At Reference Temp:

8.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0