Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-480-1214

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Unable To Decode:

Unable to decode and unable to decode

Terminal Length:

1.625 inches

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Body Diameter:

Between 0.557 inches and 0.577 inches

Body Length:

Between 1.344 inches and 1.406 inches

Body Width:

Between 0.557 inches and 0.577 inches

Body Height:

Between 0.557 inches and 0.577 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

10.0 megohms

Capacitance Value Per Section:

0.270 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-5.00 to 5.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

18000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.000

Paper Dielectric Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:

Solder

Test Data Document:

18876-9176283 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0