Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-481-4587

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

## **Terminal Length:**

1.000 inches

### **Body Diameter:**

0.191 inches

**Body Length:** 

0.500 inches

#### **Terminal Diameter:**

Between 0.010 inches and 0.030 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Anode Type:

Solid

## Impedance At Minimum Operating Tempurature In Ohms:

1.0

### **Electrical Polarization:**

Polarized

## Capacitance Value Per Section:

5.600 microfarads single section

## Nonderated Operating Temp:

85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

#### **Criticality Code Justification:**

Feat

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### Case Material:

Metal

## **Capacitive Electrode Material:**

Tantalum

# Dissipation Factor At Reference Tempurature In Percent:

10.0000

## Dc Leakage At Reference Temp:

2.000 microamperes

## **Terminal Surface Treatment:**

Solder

## **Case Insulation Material:**

Plastic

Electrolytic Fixed Capacitor - Page 2 of 2

**Special Features:** 

Burn-in test

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0

