## NSN 5910-00-483-1686

Plastic Dielectric Fixed Capacitor - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5910-00-483-1666
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
0.375 inches
Body Diameter:
0.906 inches
Body Length:
2.750 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unc
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
1000.0 megohm-microfarads
Capacitance Value Per Section:
0.250 microfarads single section
Nonderated Operating Temp:
Between -60.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.164 inches
Nonderated Continuous Voltage Rating And Type Per Section:
2000.0 dc single section
Criticality Code Justification:
Zzzy
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Glass
Insulation Resistance At Reference Temp:
100000.0 megohm-microfarads
Power Factor At Reference Tempurature In Percent:
0.9000
Terminal Type And Quantity:
2 threaded stud
Reference Number Differentiating Characteristics:
Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

N/a

Shelf Life:

## NSN 5910-00-483-1686

Plastic Dielectric Fixed Capacitor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A010b0