NSN 5910-00-483-4277

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-483-4277 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 2.000 inches **Body Diameter:** 0.145 inches **Body Length:** 0.600 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 120.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 45.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 12.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 18.0000 Dc Leakage At Reference Temp: 4.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic**

Special Features:

Designed for high reliability

NSN 5910-00-483-4277

Electrolytic Fixed Capacitor - Page 2 of 2



	Ī	erm	inal	Type	And	Quantit	y:
--	---	-----	------	-------------	-----	---------	----

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0