

View Online at <https://aerobasegroup.com/nsn/5910-00-483-6433>

Body Style:

W/mtg tabs/flanges, terminals on opposite surfaces

Reliability Indicator:

Not established

Terminal Length:

0.470 inches

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Body Length:

Between 2.110 inches and 2.200 inches

Body Width:

Between 2.110 inches and 2.200 inches

Body Height:

Between 1.150 inches and 1.220 inches

Unthreaded Mounting Hole Diameter:

Between 0.180 inches and 0.200 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.370 inches and 2.390 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Section Quantity:

3

Capacitance Value Per Section:

16.000 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

275.0 dc all sections

Tolerance Range Per Section:

-0.00 to 4.00 microfarads all sections

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Power Factor At Reference Temperature In Percent:

10.0000

Dc Leakage At Reference Temp:

0.800 milliamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0