Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-484-4176

# **Body Style:**

W/thd hol (s)/stud(s), terminal(s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.620 inches

#### **Body Length:**

1.310 inches

#### **Body Width:**

0.425 inches

# **Body Height:**

## 0.325 inches

## Center To Center Distance Between Terminals Parallel To Width:

0.200 inches

#### **Terminal Diameter:**

0.032 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.750 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

# Mounting Facility Screw Thread Series Designator:

Unc

## Mounting Facility Type And Quantity:

2 threaded mounting studs

# **Features Provided:**

Hermetically sealed case

## Capacitance Value Per Section:

0.200 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Thread Size:**

0.138 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

## Power Factor At Reference Tempurature In Percent:

1.000

## **Terminal Surface Treatment:**

Solder



Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0