NSN 5910-00-484-4959

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-484-4959

| view Offline at https://defobasegroup.com/hsh/5510-00-404-4555 |
|--|
| Body Style: |
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.000 inches |
| Body Length: |
| 0.560 inches |
| Body Width: |
| 0.440 inches |
| Body Height: |
| 0.310 inches |
| Center To Center Distance Between Terminals Parallel To Length |
| 0.400 inches |
| Terminal Diameter: |
| Between 0.024 inches and 0.029 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 500.0 megohm-microfarads |
| Capacitance Value Per Section: |
| 0.680 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -1.00/+1.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 50000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.5000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5910-00-484-4959

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| _ | | •• | • - | | | | |
|---|----|----|-----|-----|-----|-----|----|
| 1 | em | | ゖっ | riz | 2†1 | n | |
| _ | | | ıιa | 114 | au | VII | ١. |

No

Fiig:

A010b0